

LINE-INTERACTIVE UPS Axil 2000-li /1000/1000L/1500/1500L/ 2000/2000L/3000/3000L



Axil 3000(L)

Axil 2000

Axil /1000(L)
/1500(L)/2000(L)

KEY FEATURES

- Low Frequency Design With Best Stability
- Pure Sine Wave Output
- Automatic Voltage Regulation (AVR)
- User-Friendly LCD Display
- Generator Compatible
- Cold Start Function
- HID USB Communication

SPECIFICATION

Model Name	Axil 750L	Axil 1000/1000L	Axil 1500/1500L	Axil 2000/2000L	Axil 2000	Axil 3000/3000L				
Capacity	750VA/450W	1000VA/700W	1500VA/1050W	2000VA/1400W	2000VA/1400W	3000VA/2100W				
Input										
Nominal Voltage	220-240Vac									
Voltage Range	165-290Vac									
Frequency	50Hz/60Hz (Auto Sensing)									
Output										
Nominal Voltage(Batt.mode)	220-240Vac									
Frequency(Batt.mode)	50Hz/60Hz ±1%									
Waveform (Batt.mode)	Pure Sine Wave									
THDv	<5% @ Linear Load; <10% @No-Linear Load									
Transfer Time	4ms typical									
Overload Protection	Circuit breaker or inner firmware protection									
Battery										
Battery Voltage	12V	24V				24V	48V			
Battery Type	Depending on external batteries	12V/7Ah	Depending on external batteries	12V/9Ah	Depending on external batteries	12V/9Ah	Depending on external batteries			
Total Battery Quantity		2	2	2	2	2	4			
Recharge Time (to 90%)		4H	4H	4H	4H	4H	4H			
Charging Current	10A	1A	10A	1A	10A	1A	10A			
Indicators										
Display	LCD									
Alarm	Batt. Mode, low battery, overload, fault, etc.									
Interface										
RS232	Yes									
HID Compliant USB Port	Yes									
SNMP	Yes									
EPO	Yes									
RJ45/RJ11	Optional									
Management										
Auto Recharge	Yes									
Auto Restart	Yes									
Power Management Software	Yes									
Physical										
Dimension(WxHxD)(mm)	140 x 191 x 327				151 x 225 x 394	196x342x416				
Net Weight (kg)	8.2	13.5	8.3	14.4	10.2	14.4	12.5	17.7	25	22.1
Environment										
Operating Humidity	0-90% non-condensing									
Operating Temperature	0-40°C									